

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | | | |
|--|--|---|--|--|
| (51) International Patent Classification ⁶ : B27B 31/04, B65G 47/22 | A1 | (11) International Publication Number: WO 97/30830 | | |
| (21) International Application Number: PCT/SE97/00234 (22) International Filing Date: 14 February 1997 (14.02.97) | (43) International Publication Date: 28 August 1997 (28.08.97) | (81) Designated States: CA, PL, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). | | |
| (30) Priority Data: 9600714-1 26 February 1996 (26.02.96) SE (71) Applicant (for all designated States except US): C. GUNNARSSONS VERKSTADS AB [SE/SE]; Olvågen, S-340 30 Vislanda (SE). (72) Inventor and (75) Inventor/Applicant (for US only): GUNNARSSON, Cenneth [SE/SE]; Våxjövägen, S-340 30 Vislanda (SE). (74) Agent: WALLENGREN, Yngvar, Patentbyrå Y. Wallengren AB, P.O. Box 116, S-331 21 Värnamo (SE). | Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. | | | |
| (54) Title: A METHOD AND AN APPARATUS FOR TURNING BOARDS | | | | |
| | | | | |
| <p>(57) Abstract</p> <p>A method of turning boards (2) comprises the steps that the boards (2) are transported on a conveyor (1) with conveyor dogs (4), with their longitudinal direction transverse to the conveyor (1). The boards (2) are accelerated relative to the conveyor (1) until the front edges (13) of the boards (2) abut against the rear edge (14) of the next dog (4). Lifting devices (16) which move synchronously with the conveyor (1) lift the front edges of the boards (2) at the same time as the boards (2) are moved towards the lifting devices (16), whereby the boards (2) are turned with their front edges facing upwards and backwards. An apparatus for turning boards comprises a first conveyor (1) with dogs (4) for transport of the boards (2), and a second conveyor (11) with an upper part (12) which, on the first conveyor (1), shunts the boards from one dog (4) to the next. The lifting devices (16) are disposed to move synchronously with the first conveyor (1) and gradually to be raised immediately behind the dogs (4) of the first conveyor.</p> | | | | |

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | |
|----|--------------------------|----|---------------------------------------|----|--------------------------|
| AM | Armenia | GB | United Kingdom | MW | Malawi |
| AT | Austria | GE | Georgia | MX | Mexico |
| AU | Australia | GN | Guinea | NE | Niger |
| BB | Barbados | GR | Greece | NL | Netherlands |
| BE | Belgium | HU | Hungary | NO | Norway |
| BF | Burkina Faso | IE | Ireland | NZ | New Zealand |
| BG | Bulgaria | IT | Italy | PL | Poland |
| BJ | Benin | JP | Japan | PT | Portugal |
| BR | Brazil | KE | Kenya | RO | Romania |
| BY | Belarus | KG | Kyrgyzstan | RU | Russian Federation |
| CA | Canada | KP | Democratic People's Republic of Korea | SD | Sudan |
| CF | Central African Republic | KR | Republic of Korea | SE | Sweden |
| CG | Congo | KZ | Kazakhstan | SG | Singapore |
| CH | Switzerland | LI | Liechtenstein | SI | Slovenia |
| CI | Côte d'Ivoire | LK | Sri Lanka | SK | Slovakia |
| CM | Cameroon | LR | Liberia | SN | Senegal |
| CN | China | LT | Lithuania | SZ | Swaziland |
| CS | Czechoslovakia | LU | Luxembourg | TD | Chad |
| CZ | Czech Republic | LV | Latvia | TG | Togo |
| DE | Germany | MC | Monaco | TJ | Tajikistan |
| DK | Denmark | MD | Republic of Moldova | TT | Trinidad and Tobago |
| EE | Estonia | MG | Madagascar | UA | Ukraine |
| ES | Spain | ML | Mali | UG | Uganda |
| FI | Finland | MN | Mongolia | US | United States of America |
| FR | France | MR | Mauritania | UZ | Uzbekistan |
| GA | Gabon | | | VN | Viet Nam |

WO 97/30830

PCT/SE97/00234

1

A METHOD AND AN APPARATUS FOR TURNING BOARDS

TECHNICAL FIELD

5 The present invention relates to a method of turning boards which are transported with their longitudinal direction transverse to the direction of movement of a conveyor with uniformly spaced conveyor dogs, the boards being at least partly driven by the front sides of the dogs in abutment against the rear edges of the boards.

10

The present invention also relates to an apparatus for turning boards and comprises a first conveyor with uniformly spaced conveyor dogs for transport of the boards with their longitudinal direction transverse to the direction of movement of the conveyor.

15

BACKGROUND ART

In the refining of timber in the form of boards in sawmills, planing mills, furniture factories or the like, it is often necessary that the boards be turned upside down between different working operations or in order to carry out quality inspection. Situations also arise when only certain boards in a batch are to be turned over. Such turning of boards has hitherto largely been carried out manually.

25 PROBLEM STRUCTURE

The present invention has for its object to devise the method disclosed by way of introduction such that it permits a fully automatic turning of the boards upside down. The present invention also has for its object to devise the method such that only certain boards included in a batch are turned over. The present invention further has for its object to devise the method such that the boards may be handled at great speed and with a high degree of reliability without being damaged.

35 The present invention also has for its object to design the apparatus intimated by way of introduction such that it is capable of turning all or only

WO 97/30830

PCT/SE97/00234

2

certain boards included in a batch at great speed and with a high degree of reliability, that the apparatus is simple and operationally reliable and is also economical in manufacture and in operation.

5 SOLUTION

10 The objects forming the basis of the present invention in respect of the method will be attained if the method is characterized in that the boards are moved forwards in a direction of movement in relation to the conveyor such that the front edges of the boards are brought to the region of the rear side of the next dog in the conveyor, that lifting devices which are moved synchronously with the conveyor are brought into engagement with the undersides of those boards which are to be turned in the region at their front edges, that the lifting devices are gradually raised, and that the boards are
15 subjected to a force in relation to the lifting devices forwardly in their direction of movement, whereby the boards are caused to turn over with their front edge facing upwards/rearwards.

20 The objects forming the basis of the present invention in respect of the apparatus will be attained if this is characterized by at least one second conveyor which is substantially parallel with the first and has an upper part at a slightly greater height than the upper part of the first conveyor, the second conveyor operating at greater speed of movement than the first, and a number of lifting devices which are disposed to move synchronously with
25 the first conveyor and to be liftable in the region behind the dogs of the first conveyor.

30 Further advantages will be attained according to the present invention if the method is also given one or more of the characterizing features as set forth in appended subclaims 2 to 7 and if the apparatus is given one or more of the characterizing features as set forth in appended subclaims 9 to 16.

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

35 The present invention will now be described in greater detail hereinbelow, with reference to the accompanying Drawings. In the accompanying

WO 97/30830

PCT/SE97/00234

3

Drawings:

Fig. 1 schematically illustrates an apparatus for turning boards, seen from the side, i.e. in the longitudinal direction of the boards; and

Fig. 2 is a top plan view of the same apparatus as in Fig. 1.

DESCRIPTION OF PREFERRED EMBODIMENT

The apparatus according to the invention comprises a first conveyor 1 which is intended for transporting boards 2 in a transport direction 3, from the right to the left in the Figures. The first conveyor has a number of uniformly spaced dogs 4 which, with their front sides 5, shunt the boards ahead of them in engagement with the rear edges 6 of the boards. In such instance, transport of the boards 2 takes place with the longitudinal direction of the boards transverse to the longitudinal direction of the first conveyor and transverse to the transport direction 3. Preferably, the longitudinal directions of the boards extend at right angles to both the transport direction 3 and the longitudinal direction of the conveyor 1.

The first conveyor may include a number, preferably at least two, of parallel-running chains, straps, belts or the like which are provided with the above-disclosed dogs. The number of such chains etc., depends on the length of those boards which are to be transported. Fig. 2 shows two such chains or the like.

The chains, straps or belts included in the first conveyor 1 run over wheels 7 and 8 which are supported on rotary shafts 9 and 10.

In addition to the chains, straps or belts included in the first conveyor, this conveyor may further include a number of longitudinally (along the transport direction 3) disposed slide rails which vertically support the boards 2 being transported. Instead of, or as a supplement to such slide rails, the chains etc. in the first conveyor may possibly have their upper regions supported in longitudinal guides which may also carry the weight of the

WO 97/30830

PCT/SE97/00234

4

boards.

The above disclosures as regards the cooperation of the first conveyor with the advanced boards applies at the infeed end of the conveyor and at its
5 discharge end, i.e. at its right-hand and left-hand end, respectively. Along the central region of the conveyor, i.e. along a turning zone, the situation is different in that the first conveyor here at least partly functions as a brake which prevents the boards 2 in the transport direction 3 from being displaced past predetermined positions, as will be described in greater detail
10 hereinbelow.

Within the turning zone, there is provided a second conveyor 11 which is also designed as a chain conveyor, strap conveyor or belt conveyor or the like. The second conveyor suitably has the same number of chains, straps or
15 belts as the first conveyor, and these are disposed along and substantially parallel with the corresponding chains etc. in the first conveyor 1. The number of such chains etc. is adapted to the length of the boards 2 in the same manner as that which applies to the first conveyor.

20 The second conveyor 11 has its upper part 12 located at a slightly greater height than the upper part of the first conveyor 1. Further, the chains, straps or belts in the second conveyor are of a material which affords good friction against the boards 2. Hereby, the second conveyor (which advances at a greater transport speed than the first conveyor 1) will subject the boards to a
25 force in the transport direction 3 relative to the first conveyor. This implies that the boards 2 within the turning zone, i.e. the longitudinal extent of the second conveyor 11, will be given higher speed by the second conveyor, so that the boards, with their front edges 13, will come into abutment against the rear edge 14 of the immediately preceding dog 4. This is clearly apparent
30 at the right-hand end of the second conveyor 11 in Fig. 1.

That disclosed above in respect of the slide rails, longitudinal guides etc. in connection with the first conveyor 1 applies with equal analogy also to the second conveyor 11. It should also be observed that, regardless of the
35 detailed design of these slide rails, guides, etc., it applies that the second conveyor carries the boards 2 at a height level which is slightly higher than

WO 97/30830

PCT/SE97/00234

5

the first conveyor.

The width of the open space between adjacent dogs 4 on the first conveyor 1 is, for reasons which will be apparent below, approximately twice as large as the maximum width of the boards 2 which are to be turned.

Within the turning zone, i.e. within the longitudinal extent of the second conveyor 11, there is provided a third conveyor 15. This is disposed along and beside the first conveyor 1 and preferably has the same number of chains, straps, belts or the like as the first conveyor. The third conveyor 15 is provided with a number of lifting arms or lifting devices 16 which move synchronously with the first conveyor in its transport direction 3. The lifting devices 16 are disposed behind the rear edges 14 of the dogs 4 and are disposed to be liftable within the turning zone.

In such cases where all boards 2 are to be turned, the lifting devices 16 may be fixedly disposed on the third conveyor 15 in positions relative thereto which are shown along the upper part of the third conveyor 15 in Fig. 1. This implies that, because of the upward inclination in the transport direction 3, the lifting devices 16 will be gradually raised within the turning zone.

In such cases where only certain boards 2 included in a batch are to be turned, the lifting devices 16 are movably disposed on the third conveyor 15, as will be described in greater detail hereinbelow.

It will be apparent from Fig. 1 that a lifting device 16a has just come into engagement with the underside of a board which, with its front edge, abuts against the rear edge 14 of a dog 4. The next lifting device 16b has raised the front portion of the board up and begins to turn the board over, with its front edge facing backwards. This turning of the board is facilitated by the fact that the second conveyor 11 subjects the board to a force in the direction of the transport direction of the first conveyor, i.e. in the direction of the arrow 3. This force is generated by the second conveyor 11 in that this moves more quickly than the lifting devices 16 so that the boards are shunted against the lifting devices. As a result of this force, the turning or rotation of the board about its longitudinal axis is facilitated and supported. The lifting device 16c

WO 97/30830

PCT/SE97/00234

6

has just raised the front edge of the board so high that the board loses its balance and is pivoted down backwards on the conveyor 11. For this backward pivoting of the board to be possible, the distance between adjacent dogs 4 should be approximately twice as large as the maximum width of turned boards. It will further be apparent from Fig. 1 that the lower edge of the board, which rests on the second conveyor, has been displaced in the direction of the arrow 3, for which reason the lifting device 16c no longer engages with the front edge of the board, now turned to face upwards, but instead with the central portion of the original underside of the board.

10

Once the board has been finally turned upside down by the lifting device 16c, it will once again be given increased speed in relation to the first conveyor 1, which is shown straight above the drive wheel 17 of the second conveyor 11.

15

The third conveyor 15 is carried by shafts 18 and 19 which are located at different heights so that the upper part of the third conveyor will thereby slope upwards in its direction of movement, whereby the lifting devices 16 which follow the upper part of the third conveyor will gradually be raised.

20

In order to permit turning of only certain boards included in a timber batch, the lifting devices 16 are suitably not permanently fixed in relation to the third conveyor 15, but are secured in sleeves 20 which have their longitudinal axes parallel with the parts of the third conveyor 15. The lifting devices 16 are pivotal in these sleeves, for which reason the lifting devices 16a, 16b and 16c are pivotal in accordance with the double headed arrow 21 about the pivot axis 24. Along the lower part, the lifting devices 16 are naturally pivotal in a corresponding manner about an axis which is parallel with the lower part of the conveyor.

30

The anchorage of the lifting devices 16 in the sleeves 20 disposed on the third conveyor is pivotal and without defined stops, for example in that the lifting devices have conical portions which, under spring bias, are axially pressed into corresponding conical apertures in the sleeves 20.

35

At the return areas of the third conveyor 15, there are provided guide rails or

WO 97/30830

PCT/SE97/00134

7

guides 22 and 23, where the guide 23 is disposed to open out the lifting devices 16 which, along the lower part of the conveyor, are collapsed to a state approximately parallel with the shafts 18 and 19, to outwardly pivoted activated, upstanding positions which are shown along the upper part of the conveyor. The guide 23 is movable between an active and opened position where it pivots out the lifting devices 16 and a passive, collapsed position where the lifting devices may pass without hindrance and without being pivoted out to the active positions which are shown along the upper part of the third conveyor. The guide 23 is coupled to a suitable prime mover for permitting pivoting of all or only certain of the lifting devices, corresponding to turning of all boards or only certain boards, respectively.

The guide 22 at the upper end of the third conveyor is designed for opposite pivoting of the lifting devices 16, i.e. for downward pivoting of them from the upstanding, active positions along the upper part of the conveyor to collapsed, substantially horizontal positions along the lower part of the conveyor.

The above-described apparatus operates as follows:

Boards 2 are fed in at the right-hand end of the first conveyor 1 and rest thereon or along slide rails or guides disposed with the conveyor. The boards 2 are driven by the conveyor 1, at least along a certain part of its length, in that the rear edges 6 of the boards abut against the front sides 5 of the dogs 4 of the conveyor 1. When the boards 2 have arrived at the turning zone, i.e. the longitudinal extent of the second conveyor 11, the boards are displaced forwards in the transport direction 3 in relation to the first conveyor 1. In such instance, the front edges 13 of the boards will strike the rear edges 14 of the dogs 4 and be held urged against them, at least along a certain portion of movement length of the second conveyor. The lifting devices 16 are brought into engagement with the undersides of the boards 2 in the region of their front edges 13. The lifting devices 16 are disposed to move synchronously with the first conveyor 1 and are located in the region immediately behind, or at least in the proximity behind the rear edges 14 of the dogs 4. Those lifting devices 16 which are to turn boards are disposed to be raised gradually so that the front edge portions of the boards 2 are thereby

WO 97/30830

PCT/SE97/00234

8

lifted up. At the same time, the boards are subjected to a force relative to the first conveyor and the lifting devices, the direction of this force corresponding to the transport drive direction 3 of the first conveyor. Hereby, the boards 2 will be displaced in the transport direction at the same time as their forward edge portions are lifted and braked and their rear/lower edges which rest on the upper part 12 of the second conveyor 11 are subjected to a shunting force so that the boards are thereby turned over with their front edges facing upwards and backwards so far that the boards are tilted backwards, with the original upper side facing downwards on the upper part 12 of the second conveyor 11.

In order to ensure the above-mentioned engagement or force between the boards 2 and the upper part 12 of the second conveyor 11, the boards are lifted by this upper part in relation to the level of the upper part of the first conveyor 1.

Once the lifting devices 16 have turned the boards, they are once again lowered to passive positions unless the intention is to turn all boards 2 included in a batch, since the lifting devices 16 are then suitably left in their opened, active positions or alternatively are fixedly mounted on the third conveyor 15. During their movements in the opened, active position, the lifting devices follow a path which is defined by a third conveyor 15 and which makes an acute angle with the movement direction of the first and second conveyors.

The present invention may be modified without departing from the spirit and scope of the appended Claims.

WO 97/30830

PCT/SE97/00234

9

WHAT IS CLAIMED IS:

1. A method of turning boards which are transported with their longitudinal direction transverse to the direction of movement (3) of a first conveyor (1) provided with uniformly spaced conveyor dogs (4), the boards (2) being at least partly driven by the front sides (5) of the dogs in abutment against the rear edges (6) of the boards, characterized in that the boards (2) are moved forwards in the direction of movement (3) in relation to the first conveyor (1) such that the front edges (13) of the boards are brought to the region of the rear side (14) of the next dog in the conveyor; that lifting devices (16) which are moved substantially synchronously with the conveyor (1) are brought into engagement with the undersides of those boards which are to be turned in the region of their front edges (13); that the lifting devices are gradually raised; and that the boards are subjected to a force in relation to the lifting devices forwardly in their direction of movement (3), whereby the boards are caused to be turned over with their front edge facing upwards/rearwards.
2. The method as claimed in Claim 1, characterized in that the boards (2) in their forward displacement (3) relative to the first conveyor (1) are lifted slightly therefrom.
3. The method as claimed in Claim 1 or 2, characterized in that the lifting devices (16) are lowered after turning of the boards (2).
4. The method as claimed in any of Claims 1 to 3, characterized in that at least one lifting device (16) is brought into engagement with each board (2); and that this lifting device is caused to follow the board up to turning thereof.
5. The method as claimed in any of Claims 1 to 4, characterized in that the boards (2) in their forward movement (3) relative to the first conveyor (1) and in their force action relative to the lifting devices (16) are acted on by at least one second conveyor (11).
6. The method as claimed in Claim 5, characterized in that the boards

WO 97/30830

PCT/SE97/00234

10

(2) are lifted slightly by the second conveyor (11) relative to the first (1).

7. The method as claimed in any of Claims 1 to 6, characterized in that the lifting devices (16) are carried by a third conveyor (15) which, in a vertical plane, makes an acute angle with the first conveyor (1).

8. An apparatus for turning boards comprising: a first conveyor (1) with uniformly spaced conveyor dogs (4) for transport of the boards (2) with their longitudinal direction transverse to the direction of movement (3) of the conveyor, characterized by at least one second conveyor (11) which is substantially parallel with the first (1) and has an upper part (12) at a slightly greater height than the upper part of the first conveyor, the second conveyor operating at greater speed of movement than the first, and a number of lifting devices (16) which are disposed to move synchronously with the first conveyor and to be liftable in the region behind the dogs of the first conveyor.

9. The apparatus as claimed in Claim 8, characterized in that said lifting devices (16) are disposed on a third conveyor (15).

10. The apparatus as claimed in Claim 8 or 9, characterized in that the first (1), the second (11) and the third (15) conveyors are disposed side-by-side.

11. The apparatus as claimed in any of Claims 9 or 10, characterized in that the third conveyor (15), seen in a vertical plane along its movement direction, makes an acute angle with the first (1) and the second (11) conveyors.

12. The apparatus as claimed in any of Claims 8 to 11, characterized in that said lifting devices (16) are fixedly disposed on the third conveyor (15).

13. The apparatus as claimed in any of Claims 8 to 11, characterized in that said lifting devices (16) are pivotally secured on the third conveyor (15) and are pivotal about pivot axes (24) which are substantially parallel with the parts of said third conveyor, the distances between adjacent lifting

WO 97/30830

PCT/SE97/00234

11

devices (16) substantially corresponding to the distance between adjacent dogs (4).

14. The apparatus as claimed in any of Claims 8 to 13, characterized in that the free spaces between adjacent dogs (4) are approximately of the same size as twice the width of those boards (2) which are to be turned.

15. The apparatus as claimed in any of Claims 9 to 14, characterized in that at the end regions of the third conveyor (15), there are disposed guide rails or abutments (22, 23) for outward pivoting of the lifting devices (16) to active positions at the beginning of the conveyor and for downward pivoting thereof to passive positions at the end of the conveyor.

16. The apparatus as claimed in Claim 15, characterized in that the abutment (23) at the beginning of the third conveyor (15) is movable between an active position where it pivots out passing lifting devices (16) to their active positions, and a passive position where lifting devices pass unhindered in their passive positions.

WO 97/30830

PCT/SE97/00234

1/2

3
↓




Fig 1

SUBSTITUTE SHEET (RULE 26)

WO 97/30830

PCT/SE97/00134

2/2




Fig 2

SUBSTITUTE SHEET (RULE 26)

1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00234

| A. CLASSIFICATION OF SUBJECT MATTER | | |
|---|--|---|
| IPC6: B27B 31/04, B65G 47/22 According to International Patent Classification (IPC) or to both national classification and IPC | | |
| B. FIELDS SEARCHED | | |
| Minimum documentation searched (classification system followed by classification symbols) | | |
| IPC6: B27B, B65G | | |
| Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched | | |
| SE,DK,FI,NO classes as above | | |
| Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) | | |
| C. DOCUMENTS CONSIDERED TO BE RELEVANT | | |
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| X | DE 3546087 A1 (MASCHINENFABRIK ESTERER AG), 25 June 1987 (25.06.87) -- | 1-16 |
| A | SE 421505 B (RENHOLMENS MEKANISKA VERSTAD AB), 4 January 1982 (04.01.82) -- | 1-16 |
| A | US 4484675 A (DOHERTY ET AL), 27 November 1984 (27.11.84) -- | 1-16 |
| A | US 3426882 A (W.J. KORTH), 11 February 1969 (11.02.69) -- | 1-16 |
| <input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex. | | |
| * Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to undermind the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family | | |
| Date of the actual completion of the international search | | Date of mailing of the international search report |
| 6 June 1997 | | 16 -06- 1997 |
| Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86 | | Authorized officer Eddy Leopold Telephone No. +46 8 782 25 00 |

Form PCT/ISA/210 (second sheet) (July 1992)

2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00234

| C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT | | |
|---|--|-----------------------|
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| A | US 2686603 A (J.M. LAWSON), 17 August 1954 (17.08.54) -- | 1-16 |
| A | DE 3150375 A1 (AHLSTRÖMFÖRTAGEN SVENSKA AB HAMMARS MEKANISKA VERSTAD), 11 November 1982 (11.11.82) -- ----- | 1-16 |

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT
Information on patent family membersInternational application No.
PCT/SE 97/00234

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|----------------------------|---------------------|
| DE 3546087 A1 | 25/06/87 | NONE | |
| SE 421505 B | 04/01/82 | SE 7611759 A | 23/04/78 |
| US 4484675 A | 27/11/84 | NONE | |
| US 3426882 A | 11/02/69 | NONE | |
| US 2686603 A | 17/08/54 | NONE | |
| DE 3150375 A1 | 11/11/82 | SE 424282 B | 12/07/82 |

Form PCT/ISA/210 (patent family annex) (July 1992)